

**VIKING** ACCESS SYSTEMS™

SWING GATE AUTOMATION WITH A SMALL PROFILE



**X-9**

RESIDENTIAL AND COMMERCIAL

# SWING GATE OPERATOR

CLASS I, CLASS II, CLASS III, AND CLASS IV VEHICULAR GATE OPERATOR



# X-9™ PRODUCT INFORMATION AND SPECIFICATIONS

The standard specifications and features of the X-9™ gate operator showcase the commitment made in its concept and design. Whether it's the simple, clean installation, energy efficient operation, or advanced battery backup function, this operator stands alone in its class. Included with the standard package are high quality direct burial cable, the complete control center and the X-9™ operator. This operator is UL Listed 18TC UL325 and UL991.



-  **VIKING BLUE ENABLED**
-  **SOLAR EFFICIENT OPERATION**

Operational Voltage	... 24 VDC with 1/2 H.P. Motor
Main Power Source	... 120 / 220 VAC Single Phase
Battery	... 7 AmpHr 12 VDC x 2
Max Gate Capacity	... 600 lbs. / 14 feet
Max Operating Speed	... 10-13 seconds per 90°
Battery Backup Operation	... 800 Full Cycles (600 lbs. / 12' gate)
Max Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 4° F to + 158° F



**Power Door Products**  
 (914) 698-5083  
[www.PowerDoorProducts.com](http://www.PowerDoorProducts.com)

**3 YEAR RESIDENTIAL / 2 YEAR COMMERCIAL WARRANTY**