

NEW



SLIDE GATE OPERATOR

700LBS CAPACITY



RESIDENTIAL
CLASS I VEHICULAR SLIDE GATE OPERATOR



New "VFlex" Control Board

Diagnostic Display

Fail-Safe Secure

Digital Limits for Easy Set-up

Built-in Heater - Cold Weather Operation Down to -20°F

- Convenient Fuse Access
- L.E.D. status indicators
- Convenient Power Switch
- E-Z Set-Up 115V/230V

New Chassis Design



COMPATIBLE WITH VIKING WIRELESS PRODUCTS

- Wireless Master/Slave Kit provides secure and reliable wireless communication.
- Remote access to the control board settings, programming, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible handheld device.
- Plug & Play connection for the Viking wireless expansion products.



BATTERY BACKUP INCLUDED

- Standard Battery Backup provides 100 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operations, maximizing battery life.



LIGHTNING PROTECTION

- Advanced lightning strike protection up to 20,000 volts / 10,000 amps.
- On board surge protection monitoring.



DIGITAL LIMITS

- Simple, push button limit setup.
- Adaptive Digital Limit control maintains open and close limit position during changing environments and power failures



PROTECTION

- New Redesigned Chassis with Multi-Layer Corrosion Protection
- G90 Galvanized
 - Clear Zinc Plating
 - UV Rated Powder coating



INTEGRATED HEATER

- Built-in heater for operating temperatures down to -20°F.
- This will allow you run your operator in the coldest conditions.



SOLAR SMART

- Power Saving technology minimizes current draw while at standby.



DIAGNOSTICS DISPLAY

- On-board LCD screen displays voltages, amps, gate status and diagnostics.



Operational Voltage ...24 VDC

Main Power Source Options ...115 / 230 VAC Single Phase
24 AC/DC Solar Compatible

Battery ...12 VDC x 2

Max Gate Capacity ...700 lbs / 30'

Operating Speed ...12" per second

Battery Backup ...100 full continuous duty cycles (700lbs)

Maximum Duty Cycle ... 100% Continuous Cycle

Operating Temperature ... - 20° F to + 160° F



Power Door Products

(914) 698-5083

www.PowerDoorProducts.com