



## NEXX NXG-300 – Quick Start Instructions

### **BEFORE INSTALLATION**

- Make sure you have the customer's Wi-Fi network and password before starting.
- A video tutorial of the installation process can be found at <https://getnexx.com/products/nexx-smart-wi-fi-garage-door-controller-nxg-300>

### **WHAT COMES IN THE BOX**



### **SET UP AND INSTALLATION**

- Make sure you are close to the router and have a strong Wi-Fi signal for the device to work properly.
- Install the NEXX HOME mobile app on the end user's phone. QR code to download the app can be found in the manual included in the box.
- Open the NEXX HOME app and create an account.
- Connect power supply to the NEXX device.
- Once you have a steady ORANGE ACTIVITY light, log in to the NEXX HOME app and tap the "+" button on the top right of the screen to add a device.
- Follow the prompts on the screen to configure the account and complete the set-up process.

## CONNECTING THE NEXX DEVICE TO THE GATE OPERATOR

- You will need to identify which limit switch is the close limit. The “Door Sensor” wires will connect to these terminals on the board.
- Connect the provided wire harnesses to the “Opener” (RADIO and COMMON) and “Door Sensor” (CLOSE LIMIT and COMMON) ports on the back of the device. Please note polarity does matter when connecting the wires to the board.
- You will find a sticker identifying which wire from the device connects to what terminal on the operator circuit board. Please see pictures below.



Please call All-O-Matic Tech Support at (818) 787-1988 with any questions.  
Tech Support is available Monday-Friday from 7:00 am to 3:30 pm.



## NEXX NXG-300 – Quick Start Instructions

### **BEFORE INSTALLATION**

- Make sure you have the customer's Wi-Fi network and password before starting.
- A video tutorial of the installation process can be found at <https://getnexx.com/products/nexx-smart-wi-fi-garage-door-controller-nxg-300>

### **WHAT COMES IN THE BOX**



### **SET UP AND INSTALLATION**

- Make sure you are close to the router and have a strong Wi-Fi signal for the device to work properly.
- Install the NEXX HOME mobile app on the end user's phone. QR code to download the app can be found in the manual included in the box.
- Open the NEXX HOME app and create an account.
- Connect power supply to the NEXX device.
- Once you have a steady ORANGE ACTIVITY light, log in to the NEXX HOME app and tap the "+" button on the top right of the screen to add a device.
- Follow the prompts on the screen to configure the account and complete the set-up process.

## CONNECTING THE NEXX DEVICE TO THE GATE OPERATOR

- You will need to identify which limit switch is the close limit. The “Door Sensor” wires will connect to these terminals on the board.
- Connect the provided wire harnesses to the “Opener” (RADIO and COMMON) and “Door Sensor” (CLOSE LIMIT and COMMON) ports on the back of the device. Please note polarity does matter when connecting the wires to the board.
- You will find a sticker identifying which wire from the device connects to what terminal on the operator circuit board. Please see pictures below.



Please call All-O-Matic Tech Support at (818) 787-1988 with any questions.  
Tech Support is available Monday-Friday from 7:00 am to 3:30 pm.